



## HandPunch® 2000 XL

# Biometric Time & Attendance Terminal

### Put your hands on the accurate, affordable solution.

Schlage now brings the accuracy and convenience of biometric technology easily within reach of any time and attendance applications. In operations that range from coal mines to clean rooms, Schlage have proven themselves to be a practical and precise solution. Our terminals are so affordable, it doesn't make sense to consider any other technology.

### Smarter than card-based terminals

There are no cards to create, administer, carry, or lose. The HandPunch® 2000 XL verifies employees' identities in less than one second, based on the unique size and shape of their hands. HandPunch clearly notifies each user of a match using red and green indicator lights. Because no one can punch in or out for your employees, the system reduces time theft and improves payroll accuracy.

### Versatile and programmable

Programmable beyond a simple time clock, the HandPunch provides definable data management keys that allow data collection when employees punch. The systems transmit data to the time and attendance host PC through a variety of options, depending on the model. Model differences let you tailor the right system for your company's size and needs. When you want to cut time and attendance costs...do it by hand.

### **Break Compliance**

The new line of biometric HandPunch readers that is now capable of complying with labor "Meal" laws that have been adopted by more than 20 states. These labor laws are in place to regulate on-the-job meals and breaks for employees. Thanks to AMG Time Attendance Software, the Schlage HandPunch 2000 XL "Break Compliance" capability will make it possible for employers to comply with laws relating to meals and breaks, avoiding potential fines and lawsuits.



### **Features and Benefits**

- Saves money over card-based systems
- Eliminates badges
- Eliminates buddy punching
- · Fast and easy to use
- Provides the most accurate time and attendance solution available.



### HandPunch® 2000 XL

### **Hand Geometry Technology**

The HandPunch 2000 XL uses Schlage's field-proven hand geometry biometric technology. The terminal captures an image of the hand each time the employee punches. The hand's size and the shape are used to verify their identity with unparalleled accuracy. No fingerprints or palm prints are utilized. Green and red lights notify the employee of the status of each punch. There's no question any more; employees have to be there to punch.

### **Programmable Data Management Keys**

The HandPunch 2000 XL has two user-definable data management keys that let you collect data as employees punch. Common uses include department transfers, tips collected, job codes, or pay codes. Multilevel data entry sequences may be defined. You can also set the data management keys to allow employees to review their past punches. To reduce keystrokes, the keys can also be set to automatically enter data such as a frequently used department number or in/out status.

### **Communication Options**

The HandPunch 2000 XL connects quickly to the time and attendance sysatem via RS-232 communications. An optional Ethernet module or dial-up high speed modem is available for alternative communication options.

#### **Antimicrobial Protection**

Every HandPunch conttain a silver-based antimicrobial agent - which is embedded into the materials used to produce the platen, providing a finish that inhibits the growth of a broad spectrum of bacteria, mold, and fungi and remains active for the life of the HandPunch.

### **Hand Outline**

The HandPunch comes standard with a blue hand outline printed on the platen. This hand outline will help new users place their hand accurately on the platen when using the terminal and decrease initial enrollment time.

Specifications	
Part Number	HP-2000 XL
Size	8.85 in (22.3 cm) wide 11.65 in (29.6 cm) high 8.55 in (21.7 cm) deep
Weight	6 lbs (2.7 kg)
Power	12 to 24 VDC or 12 to 24 VAC 50-60 Hz, 7 watts
Environment	Operating: 32°F to 113°F (0°C -to 45°C) Relative Humidity: 20%-80% NC Non-operating(storage): 14°F to 140°F (-10°C to 60°C) Relative Humidity: 5% to 85% NC
Verification Time	Less than one second
Memory Retension	Up to 5 years via the standard internal lithium battery.
Transaction Storage	5120 transactions
ID Number Length	1 to 10 digits from keypad or card
User Capacity	512 users
Template Size	9 bytes
Communications	RS232, 300 to 28.8 Kbps
Options	BB-250 Operational Battery Backup EN-200 Ethernet Module MD-500 Internal 14.4 Baud Dial-up Modem WAR-EXT 1 year extended warranty



